



CHEM-SEAL 14-WB

Acrylic Sealer, Hardener, and Dust Proofer

PRODUCT DESCRIPTION

CHEM-SEAL 14-WB water based sealer and dustproofer, containing 14% solid acrylic resin. The Chem-Seal 14-WB dries to a tough uniform clear non-yellowing coat. The Chem-Seal 14-WB is used in interior or exterior applications. It especially effective on exposed aggregate concrete surfaces, concrete stains, and all forms of masonry stone features.

FIELDS OF APPLICATION

- Excellent for concrete, cement mortar, wood and metal.
- Protects decorative stained concrete.
- Use over terrazzo, tiles, asbestos roofs and asphalt roof felts.
- Protective coating for spray applied polyurethane foam that is prone to ultra violet degradation.

PRODUCT FEATURES

- One component liquid.
- Waterproof and weather proof.
- Protective.
- Easy to apply by brush or airless spray.
- Excellent adhesion to concrete and steel.
- Excellent flexibility; bridges hairline cracks and small holes.
- UV Stable.

PACKAGING

Product	Packaging
CHEM-SEAL WB 14	5 Gal Pail (18.93 Liter) 55 Gal (208 Liter) Drum

TECHNICAL DATA

Property	Value at 77°F/25°C	ASTM Method
Density Lb/Gal (Kg/L)	7 (0.84)	D-1475
Freezing Temperature °F (°C)	20 (-7)	-
Coverage Ft ² /Gal (m ² /L)	200 (4.9 m ²)	-
Solid Content by Weight	14%	-
Color	White*	-

*Product Dries clear

APPLICATION DATA

Surface Preparation:

Make sure all surface waters have evaporated prior to application.

APPLICATION: Apply Chem-Seal 14-WB using a spray, brush, roller, etc. using a consistent and complete application method to the concrete surfaces to be cured and sealed. Apply Chem-Seal 14-WB after a minimum of 7 days curing if a high gloss is desired.

CLEANING

Tools, equipment, spray unit, etc. can be cleaned immediately using water only.

STORAGE

The product can be stored for minimum of twelve months at temperature from 40°F/5°C to 77°F/25°C in the unopened original packing. **Do Not allow Product to Freeze.**

TECHNICAL ASSISTANCE

Please contact International Chem-Crete Corporation for Technical Assistance.

WARRANTY

LIMITED WARRANTY: International Chem-Crete Inc. warrants that, at the time and place we make shipment, our materials will be of good quality and will conform to our published specifications in force on the date of acceptance of the order.

DISCLAIMER: The information contained herein is included for illustrative purposes only and, to the best of our knowledge is accurate and reliable. International Chem-Crete Inc. is not under any circumstances liable to connection with the use of information. As International Chem-Crete Inc. has no control over the use to which others may put its products, it is recommended that the products be tested to determine the suitability for specific applications and/or our information is valid in a particular circumstances. Responsibility remains with the architect or engineer, contractor and owner of the design, application and proper installation of each product. Specifier and user shall determine the suitability of the product for specific application and assume all responsibility in connection therewith. AM240409.

Manufactured By:



International Chem-Crete Inc., 800 Security Row, Richardson, TX 75081, U.S.A
Tel: (972) 671-6477, Fax: (972) 238-0307
contactus@chem-crete.com www.chem-crete.com