



CHEM-STRIP 95

Form Release Agent

PRODUCT DESCRIPTION

CHEM-STRIP 95 is a form release agent for use on metal, wood and fiber forms. Imparts a longer life expectancy on wood forms as well as helps keep forms clean and will allow foot traffic on metal forms prior to pouring concrete. Fiber forms are much easier to strip after a considerable period of time has elapsed.

FIELDS OF APPLICATION

CHEM-STRIP 95 can be used as form release agent for many surfaces like wood, fiber forms, steel, etc.

PACKAGING

Product	Packaging
CHEM-STRIP 95	5 GAL (18.92 Liters) PAIL
	55 GAL (208.18 Liters) DRUM

TECHNICAL DATA

Property	Value @ 25°C (77°F)
Specific Gravity	0.81
Freeze Temperature, °F (°C)	20 (-7)
Freeze Harm	None
Boiling Point, °F (°C)	130 (54)
Coverage, ft ² /gal (m ² /L)	200 (4.9)
Solvent Clean up	Mineral Spirit
Odor	Petroleum
Color	Yellow
Toxicity	None
Flammability rating	Flash @ 140°F (60°C)
Fumes During Treatment	Slight
Environmental Hazards	None

APPLICATION DATA

Preparation: clean all form surfaces prior to the application of CHEM-STRIP 95 to remove oils, dirt, rust and scale.

Application:

1. Apply **CHEM-STRIP 95** using a spray, brush, roller, etc. using a consistent and complete application method to the

concrete forms to be utilized.

2. After form removal, clean forms and repeat Step 1 to completely protect forms' surfaces.

CLEANING

Clean all tools and sprayers with Mineral Spirit.

SAFETY PRECAUTIONS

Do not allow material to come into contact with eyes, hands, glass, aluminum or glazed tile systems.

STORAGE

Store all containers between 40°F and 95 °F (5 and 35°C).

TECHNICAL ASSISTANCE

Please contact International Chem-Crete Corporation for Technical Personnel.

WARRANTY

LIMITED WARRANTY: International Chem-Crete Inc. warrants that, at the time and place we make shipment, our materials will be of good quality and will conform to our published specifications in force on the date of acceptance of the order.

DISCLAIMER: The information contained herein is included for illustrative purposes only and, to the best of our knowledge, is accurate and reliable. International Chem-Crete Inc. is not under any circumstances liable to connection with the use of information. As International Chem-Crete Inc. has no control over the use to which others may put its products, it is recommended that the products be tested to determine the suitability for specific applications and/or our information is valid in particular circumstances. Responsibility remains with the architect or engineer, contractor and owner of the design, application and proper installation of each product. Specifier and user shall determine the suitability of the product for specific application and assume all responsibility in connection therewith. AM02519.

Manufactured By:



International Chem-Crete Inc., 800 Security Row, Richardson, TX 75081, U.S.A

Tel: (972) 671-6477, Fax: (972) 238-0307

contactus@chem-crete.com

www.chem-crete.com